



OMEGA
600TS SERIES

Track scissor with levelling capabilities

- » Up to 10,2 m working height.
- » Standard double hydraulic powered extension decks - reaching a 7,1 meter deck length.
- » Easy levelling capabilities, side - side / fore - aft - manual and fully automatic controls.
- » Compact design.
- » Optional radiographic remote control.
- » Impressive lifting capacity - up to 1.500 kg.
- » Smooth and precise proportional drive control, with dual joystick controllers.
- » 37kW Diesel engine - fulfil STAGE V / TIER 4 Final standard.
- » 90 degrees hydraulic operated rotation (612TS only)

612TS / 615TS Track scissor

Specifications

	612TS	615TS
Max. working height	10,2 m	10,2 m
Max. platform height	8,2 m	8,2 m
Stowed height (top guardrails)	3,20 m	3,20 m
Stowed height (guardrails lowered)	2,85 m	2,85 m
Stowed height (guardrails removed)	2,28 cm	2,28 cm
Width	2,20 m	2,20 m
Length - stowed	4,16 m	4,16 m
Track length	3,14 m	3,14 m
Lifting capacity	1.250 kg	1.500 kg
Ground clearance	35 cm	35 cm
Platform length retracted	4,00 m	4,00 m
Platform length extended	7,10 m	7,10 m
Platform width	2,10 m	2,10 m
Drive speed stowed	2 km/h	2 km/h
Gradeability	35%	35%
Weight	8.340 kg	8.200 kg
Rotation	90 degrees hydraulic operated	N/A
Power source	KUBOTA D1803-CR-TE5B	
Levelling capabilities	5° side to side / 5° fore to aft Controls by manual - and by Auto-levelling feature	



Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.



www.omegasales.eu

Standard features

- » Up to 10,2 m working height.
- » Auto and manual levelling - 5° side / side & 5° fore / aft.
- » Double hydraulic powered extension decks - featuring a ergonomic working space of huge 7,1 meter deck length.
- » Fully proportional drive and lift control.
- » Easy maintenance access to mechanical, electrical and diesel components without raising platform or swinging out trays.
- » CE compliant & Emission STAGE V compliant.
- » 90° hydraulic turret rotation (612TS only).
- » On-Board diagnostic system.



Optional features

- » Hydraulic powered generator 380 / 230 / 110 Vac - up to 6 kW.
- » DC / AC convertor for 110V or 230Vac supply, up to 3 kW.
- » Radiographic remote control.
- » Custom colours.
- » Non-marking tracks.
- » Working lights

Leemidden 21
2678 ME De Lier
The Netherlands

+ 31 174 - 525 990
sales@omegasales.eu